

Artikel: LANO

PRODUCTEIGENSCHAPPEN KWALITEIT LANO

Quality		Tufted cut pil 1/10"
Pile layer		100% PA - 100%recycled
Primary Backing		Easy Design Fit or Actionbacking
Available Tile Size		48 x 48 cm & 96 x 96 cm
Minimal order quantity		> 100 m ²
Ware rating	EN1307	Heavy 33
Comfort rating	EN1307	LC3
Total weight	ISO 8543	ca 1989 gr/ m ²
Total thickness	ISO 1765	Ca 7,5 mm
Total pile weight		ca 1028 gr/ m ²
Pile height above primary backing	ISO 1766	ca 5 mm
Pile density	ISO 8543	ca 0,12 gr/cm ³
Number of tufts	ISO 1763	ca 217250 / m ²
Vertical resistance	ISO 6356	≤ 2kV
Impact sound reduction	ISO 140-3	ca 27 dB
sound absorption rate α _w	ISO 354	ca 0,25
thermal resistance	EN12667	ca 0,11 m ² K/W
Reaction to fire	EN 13501	Cfl-s1
CE-number		1658-CPR-3133
DoP-number		0004
Colour fastness to light	DIN EN ISO 105 B02	≥ 5
Colour fastness to water	DIN EN ISO 105 E01	≥ 4
Colour fastness to rubbing	DIN EN ISO 105 X12	≥ 3-4

